

(43) International Publication Date 23 May 2002 (23.05.2002)

PCT

(10) International Publication Number WO 02/40102 A2

- (51) International Patent Classification<sup>7</sup>:
- (21) International Application Number: PCT/US01/44256

A62D 1/00

(22) International Filing Date:

14 November 2001 (14.11.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/249,684

17 November 2000 (17.11.2000) US

- (71) Applicant (for all designated States except US): PCBU SERVICES, INC. [US/US]; Suite 1269, 300 Delaware Avenue, Wilmington, DE 19801 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ROBIN, Mark, L. [US/US]; 5415 Hillside Lane, West Lafayette, IN 47906 (US).
- (74) Agent: ANDERSON, Richard, A.; Marshall, Gerstein & Borun, 6300 Sears Tower, 233 South Wacker Drive, Chicago, IL 60606 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

EST AVAILABLE COPY

(54) Title: FIRE EXTINGUISHING METHODS UTILIZING HYDROFLUOROETHERS

(57) Abstract: Highly fluorinated, saturated and unsaturated hydrofluoroethers are efficient, economical, non-ozone-depleting fire extinguishing agents used alone or in blends with other fire extinguishing agents in total flooding and portable systems.

- 1 -

# FIRE EXTINGUISHING METHODS UTILIZING HYDROFLUOROETHERS

## FIELD OF THE INVENTION

The present invention is directed to hydrofluoroether fire extinguishing agents and methods for extinguishing fires using the hydrofluoroethers. More particularly, the present invention is directed to fire extinguishing agents and methods using saturated or unsaturated, fluorinated  $C_4$  and/or  $C_5$  hydrofluoroethers, and blends of one or more of the hydrofluoroethers with one or more other fire extinguishing agents.

### BACKGROUND OF THE INVENTION AND PRIOR ART

The use of certain bromine, chlorine and iodine-containing halogenated chemical agents for the extinguishment of fires is common. These agents are in general thought to be effective due to their interference with the normal chain reactions responsible for flame propagation. The most widely accepted mechanism for flame suppression is the radical trap mechanism proposed by Fryburg in *Review of Literature Pertinent to Fire Extinguishing Agents and to Basic Mechanisms Involved in Their Action*, NACA-TN 2102 (1950). The finding that the effectiveness of the halogens are on a molar basis in the order Cl<Br<I supports the radical trap mechanism, as reported by Malcom in *Vaporizing Fire Extinguishing Agents*, Report 117, Dept. of Army Engineering Research and Development Laboratories, Fort Bevoir, VA, 1950 (Project-8-76-04-003). It is thus generally accepted that compounds containing the halogens Cl, Br and I act by interfering with free radical or ionic species in

5

10

15

- 2 -

the flame and that the effectiveness of these halogens is in the order I > Br > Cl. In addition, it is generally thought that to be effective as a fire extinguishing agent, a compound must contain Cl, Br or I.

The use of iodine-containing compounds as fire extinguishing agents has been avoided primarily due to the expense of their manufacture or due to toxicity considerations. Until very recently, the three fire extinguishing agents presently in common use were all bromine-containing compounds, Halon 1301 (CF<sub>3</sub>Br), Halon 1211 (CF<sub>2</sub>BrCl) and Halon 2402 (BrCF<sub>2</sub>CF<sub>2</sub>Br). The effectiveness of these three volatile bromine-containing compounds in extinguishing fires has been described in U.S. Pat. No. 4,014,799 to Owens. Although not employed commercially, certain chlorine-containing compounds are also known to be effective extinguishing agents, for example Halon 251 (CF<sub>3</sub>CF<sub>2</sub>Cl) as described by Larsen in U.S. Pat. No. 3,844,354.

Although the above named bromine or chlorine-containing Halons are effective fire fighting agents, those agents containing bromine or chlorine are asserted by some to be capable of the destruction of the earth's protective ozone layer. Also, because the agents contain no hydrogen atoms which would permit their destruction in the troposphere, the agents may also contribute to the greenhouse warming effect.

More recently, hydrofluorocarbons have been proposed as fire suppression, for example in U.S. Pat. No. 5,124,053. However, a disadvantage of these compounds is their relatively high global warming potential.

5

10

10

15

20

It is therefore an object of this invention to provide a method for extinguishing fires that extinguishes fires as rapidly and effectively as the techniques employing Halon agents while avoiding the above-named drawbacks.

It is a further object of this invention to provide an agent for the use in a method of the character described that is efficient, economical to manufacture, and environmentally safe with regard to ozone depletion and greenhouse warming effects.

It is a still further object of this invention to provide blends of the new agents and other fire extinguishing agents that are effective and environmentally safe.

### SUMMARY OF THE INVENTION

The foregoing and other objects, advantages and features of the present invention may be achieved by employing saturated or unsaturated, higher fluorinated hydrofluoroethers and blends thereof with other agents as fire extinguishants for use in fire extinguishing methods and apparatus. More particularly, the method of this invention involves introducing to a fire a saturated or unsaturated, fluorinated  $C_4$  or  $C_5$  hydrofluoroether in a fire extinguishing concentration and maintaining such concentration until the fire is extinguished. Specific saturated, fluorinated  $C_4$  or  $C_5$  hydrofluoroethers of this invention include:

CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>2</sub>F, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>2</sub>F, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCHF<sub>2</sub> and (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCF<sub>3</sub>.

- 4 -

Specific unsaturated, fluorinated  $C_4$  or  $C_5$  hydrofluoroethers of the present invention include:

 $CF_3CF = CFOCH_3, \qquad CF_3CF = CFOCH_2F, \qquad CF_3CF = CFOCHF_2,$   $CF_3CF = CFOCF_3, \qquad CF_2 = CFCF_2OCH_3, \qquad CF_2 = CFCF_2OCH_2F,$   $CF_2 = CFCF_2OCF_2H, \qquad CF_2 = CFCF_2OCF_3, \qquad (CF_3)_2C = CFOCH_3,$   $(CF_3)_2C = CFOCH_2F, \qquad (CF_3)_2C = CFOCF_2H, \qquad (CF_3)_2C = CFOCF_3,$   $CF_2 = C(CF_3)CF_2OCH_3, \qquad CF_2 = C(CF_3)CF_2OCH_2F, \qquad CF_2 = C(CF_3)CF_2OCF_2H$  and  $CF_2 = C(CF_3)CF_2OCF_3.$ 

These hydrofluoroethers may be used alone, in admixture with each other or as blends with other fire extinguishing agents. Generally, the agents of this invention are employed at concentrations lying in the range of about 3 to 15%, preferably 5 to 10% in air, on a v/v basis. The agents of this invention are suitable for use in both total flooding and portable fire suppression applications. Suitable extinguishing agents ('blends') for admixture with the hydrofluoroethers include CF<sub>3</sub>CHFCF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>CF<sub>2</sub>H, CF<sub>3</sub>CH<sub>2</sub>CF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>H, and CF<sub>3</sub>H.

The hydrofluoroethers of this invention may be produced via numerous routes. For example, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H may be prepared via a three step process comprising

- 20 (i) reaction of methanol with commercially available hexafluoropropene (CF<sub>3</sub>CF=CF<sub>2</sub>) in the presence of base to produce CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>;
  - (ii) chlorination of CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub> with Cl<sub>2</sub> to produce CF<sub>3</sub>CHFCF<sub>2</sub>OCHCl<sub>2</sub>; and

- 5 -

(iii) fluorination of CF<sub>3</sub>CHFCF<sub>2</sub>OCHCl<sub>2</sub> with HF to produce the final product CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H.

By further reacting with a strong base like sodium or potassium hydroxide the corresponding unsatured  $C_4$  or  $C_5$  hydrofluoroethers may be prepared.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

In accordance with the present invention, saturated and unsaturated C<sub>4</sub> and C<sub>5</sub> hydrofluoroethers have been found to be effective fire extinguishants at concentrations safe for use. However, because such hydrofluoroethers contain no bromine or chlorine, they have an ozone depletion potential of zero. Furthermore, since the compounds are characterized by short atmospheric lifetimes they are susceptible to breakdown in the lower atmosphere and hence do not pose a threat as greenhouse warming gasses.

Specific hydrofluoroethers useful in accordance with this invention are:

. 20

5

- 6 -

These hydrofluoroethers may be used alone, in admixture with each other or as blends with other fire extinguishing agents. Generally, when a single hydrofluoroether of this invention is employed, concentrations lying in the range of about 3 to 15%, preferably 5 to 10% in air, on a v/v basis, are used; when employed in admixture, concentrations lying in the range of about 3 to 15%, preferably 5 to 10% in air, on a v/v basis, are used. Where the hydrofluoroethers of this invention are employed in admixture with other fire extinguishing agents ('blends'), the hydrofluoroethers desirably comprise of at least about 10 percent by weight of the blend, and the overall concentration of the blend lies in the range of about 3 to 15%, preferably 5 to 10% in air, on a v/v basis. The agents of this invention are suitable for use in both total flooding and portable fire suppression applications. Suitable extinguishing agents for admixture with the hydrofluoroethers include CF<sub>3</sub>CHFCF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>CF<sub>2</sub>H, CF<sub>3</sub>CH<sub>2</sub>CF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>H, and CF<sub>3</sub>H.

15

20

25

5

10

The C<sub>4</sub> or C<sub>5</sub> hydrofluoroethers of this invention may be effectively employed at substantially any minimum concentrations at which fire may be extinguished, the exact minimum level being dependent on the particular combustible material, the particular hydrofluoroether and the combustion conditions. In general, however, best results are achieved where the hydrofluoroethers or mixtures and blends thereof are employed at a level of at least about 3% (v/v). Where hydrofluoroethers alone are employed, best results are achieved with agent levels of at least about 5% (v/v). Likewise, the maximum amount to be employed will be governed by matters of economics and potential toxicity to living things. About 15% (v/v) provides a convenient maximum concentration for use of hydrofluoroethers and mixtures and blends thereof in occupied areas. Concentrations above 15% (v/v) may be employed in unoccupied areas, with the exact level being determined by the particular combustible material, the hydrofluoroether (or mixture or blend thereof) chosen

10

15

20

25

and the conditions of combustion. The preferred concentration of the hydrofluoroether agents, mixtures and blends in accordance with this invention lies in the range of about 5 to 10% (v/v).

Hydrofluoroethers may be applied using conventional application techniques and methods used for Halons such as Halon 1301 and Halon 1211. Thus, these agents may be used in a total flooding fire extinguishing system in which the agent is introduced to an enclosed region (e.g., a room or other enclosure) surrounding a fire at a concentration sufficient to extinguish the fire. In accordance with a total flooding system apparatus, equipment or even rooms or enclosures may be provided with a source of agent and appropriate piping, valves, and controls so as automatically and/or manually to be introduced an appropriate concentrations in the event that fire should break out. Thus, as is known to those skilled in the art, the fire extinguishant may be pressurized with nitrogen or other inert gas at up to about 600 psig at ambient conditions.

Alternatively, the hydrofluoroether agents may be applied to a fire through the use of conventional portable fire extinguishing equipment. It is usual to increase the pressure in portable fire extinguishers with nitrogen or other inert gasses in order to insure that the agent is completely expelled from the extinguisher. Hydrofluoroether containing systems in accordance with this invention may be conveniently pressurized at any desirable pressure up to about 600 psig at ambient conditions.

The compounds of the present invention are nondestructive agents, and are especially useful where cleanup of other media poses a problem. Some of the applications of the hydrofluoroethers of this invention are the extinguishing of liquid and gaseous fueled fires, the protection of electrical

10

equipment, ordinary combustibles such as wood, paper and textiles, hazardous solids, and the protection of computer facilities, data processing equipment and control rooms.

The invention will be further described with reference to the following specific Examples. However it will be understood that these Examples are illustrative in nature and not restrictive in nature.

#### **EXAMPLE 1**

This example demonstrates the desirable "throw" obtainable with the fire suppression agents of the present invention when employed in portable ("streaming") applications. The throw is the distance the stream of agent can be discharged; the longer the throw the better, as this allows extinguishment without approaching the fire at too close a distance, which can lead to exposure of the operator to fire and toxic fumes from the combustion process.

A 150 mL SS cylinder was equipped with an inlet tube and a dip tube connected via an on/off valve to a delivery nozzle. The cylinder was charged with 50 grams of CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H and then pressurized with nitrogen to the desired pressure. The cylinder contents were completely discharged and the throw distance noted (Table 1).

- 9 -

TABLE 1
Throw vs. Pressure for CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H System

	Pressure, psig	Throw, feet
	25	10
5	80	15
	120	17
	150	18

#### **EXAMPLE 2**

This example demonstrates the extinguishment of Class B fires with the agents of the present invention. A 150 mL SS cylinder was equipped with an inlet tube and a dip tube connected via an on/off valve to a delivery nozzle. The cylinder was charged with 30 grams of CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H and then pressurized with nitrogen to 120 psig. A 2 inch x 4 inch x 0.5 inch SS pan was filled with 20 mL of methanol. The methanol was ignited and allowed to burn for 30 seconds; the agent was then discharged from a distance of 4 feet onto the fire. The methanol fire was extinguished in 1.5 seconds; a total of 16 grams of agent was discharged.

#### **EXAMPLE 3**.

The method of Example 2 was employed with acetone, isopropanol and heptane fuels. All fires were rapidly extinguished (see Table 2).

10

PCT/US01/44256

- 10 -

TABLE 2

Extinguishment with CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H

	Fuel	Extinguishing	Agent discharged,	
		Time, seconds	grams	
	acetone	2.0	25	
5	isopropanol	1.5	21	
	heptane	1.8	11	

#### EXAMPLE 4

This example demonstrates the extinguishment of deep-seated Class A fires with the agents of the present invention. A 150 mL SS cylinder was equipped with an inlet tube and a dip tube connected via an on/off valve to a delivery nozzle. The cylinder was charged with 30 grams of CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H and then pressurized with nitrogen to 120 psig. A wood crib was constructed of six layers of 6 inch x 2 inch by 0.125 inch strips of kiln dried fir, each layer consisting of 4 pieces. The crib was soaked with heptane, ignited, and allowed to burn for five minutes. The agent was then discharged onto the fire, resulting in rapid (< 2 seconds) extinguishment; a total of 25 grams of agent was discharged. Immediately after extinguishment the wood crib was cold to the touch, demonstrating the efficient suppression afforded by the agent.

10

- 11 -

#### WHAT IS CLAIMED IS:

- 1. A method for extinguishing a fire comprising the steps of introducing to the fire a fire extinguishing concentration of a composition comprising a compound selected from the group consisting of a saturated, fluorinated  $C_4$  hydrofluoroether, a saturated, fluorinated  $C_5$  hydrofluoroether, an unsaturated, fluorinated  $C_4$  hydrofluoroether and an unsaturated, fluorinated  $C_5$  hydrofluoroether and maintaining the concentration of the compound until the fire is extinguished.
- The method of claim 1, wherein the compound is selected
  from the group consisting of CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>2</sub>F,
  CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>3</sub>,
  (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>2</sub>F, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCHF<sub>2</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCF<sub>3</sub>,
  CF<sub>3</sub>CF=CFOCH<sub>3</sub>, CF<sub>3</sub>CF=CFOCH<sub>2</sub>F, CF<sub>3</sub>CF=CFOCHF<sub>2</sub>,
  CF<sub>3</sub>CF=CFOCF<sub>3</sub>, CF<sub>2</sub>=CFCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>2</sub>=CFCF<sub>2</sub>OCH<sub>2</sub>F,

  CF<sub>2</sub>=CFCF<sub>2</sub>OCF<sub>2</sub>H, CF<sub>2</sub>=CFCF<sub>2</sub>OCF<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>C=CFOCH<sub>3</sub>,
  (CF<sub>3</sub>)<sub>2</sub>C=CFOCH<sub>2</sub>F, (CF<sub>3</sub>)<sub>2</sub>C=CFOCH<sub>3</sub>,
  CF<sub>2</sub>=C(CF<sub>3</sub>)CF<sub>2</sub>OCH<sub>3</sub>, CF<sub>2</sub>=C(CF<sub>3</sub>)CF<sub>2</sub>OCF<sub>2</sub>H and
  CF<sub>2</sub>=C(CF<sub>3</sub>)CF<sub>2</sub>OCF<sub>3</sub>.

- The method of claim 1, wherein the compound is selected from the group consisting of CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>2</sub>F, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>2</sub>F, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>3</sub>.
- 5 4. The method of claim 1, wherein the compound is employed at a level of at least about 3 % (v/v).
  - 5. The method of claim 1, wherein the compound is employed in a total flooding system.
- 6. The method of claim 1, wherein the compound is employed in a portable extinguishing system.
  - 7. The method of claim 1, wherein the composition comprises a blend with other fire extinguishing agents.
- 8. The method of claim 7, wherein the other fire extinguishing agents are selected from the group consisting of CF<sub>3</sub>CHFCF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>CF<sub>2</sub>H, CF<sub>3</sub>CH<sub>2</sub>CF<sub>3</sub>, CF<sub>3</sub>CF<sub>2</sub>H, and CF<sub>3</sub>H.

PCT/US01/44256

- A fire extinguishing agent comprising a compound 9. selected from the group consisting of CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>2</sub>F, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>3</sub>, (CF<sub>3</sub>)<sub>2</sub>CHCF<sub>2</sub>OCH<sub>3</sub>, CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H,  $(CF_3)_2CHCF_2OCH_2F$ ,  $(CF_3)_2CHCF_2OCHF_2$ ,  $(CF_3)_2CHCF_2OCF_3$ ,  $CF_3CF = CFOCH_2F$ ,  $CF_3CF = CFOCHF_2$ , 5  $CF_3CF = CFOCH_3$ ,  $CF_3CF = CFOCF_3$ ,  $CF_2 = CFCF_2OCH_3$ ,  $CF_3 = CFCF_2OCH_3$ ,  $CF_2 = CFCF_2OCF_2H$ ,  $CF_2 = CFCF_2OCF_3$ ,  $(CF_3)_2C = CFOCH_3$ ,  $(CF_3)_2C = CFOCH_2F_3$  $(CF_3)_2C = CFOCF_2H$ ,  $(CF_3)_2C = CFOCH_3$ ,  $CF_2 = C(CF_3)CF_2OCH_3$ ,  $CF_2 = C(CF_3)CF_2OCH_2F$ ,  $CF_2 = C(CF_3)CF_2OCF_2H$  and 10  $CF_2 = C(CF_3)CF_2OCF_3$ .
  - 10. A method of making CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H comprising the steps of
    - (i) reacting methanol with hexafluoropropene in the presence of base to produce CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub>;
- 15 (ii) chlorinating CF<sub>3</sub>CHFCF<sub>2</sub>OCH<sub>3</sub> with Cl<sub>2</sub> to produce CF<sub>3</sub>CHFCF<sub>2</sub>OCHCl<sub>2</sub>; and
  - (iii) fluorinating CF<sub>3</sub>CHFCF<sub>2</sub>OCHCl<sub>2</sub> with HF to produce CF<sub>3</sub>CHFCF<sub>2</sub>OCF<sub>2</sub>H.

- 11. A method of making a saturated, fluorinated  $C_4$  or  $C_5$  hydrofluoroether comprising the steps of
  - (i) reacting a C<sub>1</sub> alcohol with a fluorinated C<sub>3</sub> or C<sub>4</sub> alkene in the presence of a base to form a first reaction product;
- 5 (ii) chlorinating the first reaction product with Cl<sub>2</sub> to form a second reaction product; and
  - (iii) fluorinating the second reaction product with HF to form a saturated, fluorinated  $C_4$  or  $C_5$  hydrofluoroether.
- 12. The method of claim 11, wherein the base is selected from the group consisting of sodium and potassium hydroxide.

PCT/US 01/44256

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A62D1/00 C07C41/01 C07C43/12

According to International Patent Classification (IPC) or to both national classification and IPC

#### B. FIELDS SEARCHED

Minimum documentation searched (classification system tollowed by classification symbols) IPC 7-A62D-C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, CHEM ABS Data, COMPENDEX

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Χ	US 5 730 894 A (MINOR BARBARA HAVILAND) 24 March 1998 (1998-03-24)	1-4,7,9
Y	column 2, line 1 column 3, line 54 -column 6, line 33 column 9, line 50 - line 60; claims 1,6,7	8
X	WO 96 40834 A (DU PONT) 19 December 1996 (1996-12-19) page 5, line 9; claims 16,17	1-3,9
Υ	WO 93 24586 A (DU PONT) 9 December 1993 (1993-12-09) page 3, line 6 - line 14 page 7, line 22 - line 28; claims 1,3,4	8
·	<b>-/</b>	

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.		
<ul> <li>Special categories of cited documents:</li> <li>"A" document defining the general state of the art which is not considered to be of particular relevance</li> <li>"E" earlier document but published on or after the international filing date</li> <li>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</li> <li>"O" document referring to an oral disclosure, use, exhibition or other means</li> <li>"P" document published prior to the international filing date but later than the priority date claimed</li> </ul>	<ul> <li>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</li> <li>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</li> <li>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</li> <li>"&amp;" document member of the same patent family</li> </ul>		
Date of the actual completion of the international search	Date of mailing of the international search report		
3 January 2003	1 3. 01. 03		
Name and mailing address of the ISA  European Palent Office, P.B. 5818 Patenllaan 2  NL - 2280 HV Rijswijk  Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,	Authorized officer  Lehnert, A		
Fax: (+31-70) 340-3016			

Form PCT/ISA/210 (second sheet) (July 1992)

## (19) World Intellectual Property Organization International Bureau



# 

# (43) International Publication Date 23 May 2002 (23.05.2002)

## PCT

# (10) International Publication Number WO 02/040102 A3

- (51) International Patent Classification<sup>7</sup>: C07C 41/01, 43/12
- A62D 1/00,
- (21) International Application Number: PCT/US01/44256
- (22) International Filing Date:

14 November 2001 (14.11.2001)

(25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data: 60/249,684 17 November 2000 (17.11.2000) US
- (71) Applicant (for all designated States except US): PCBU SERVICES, INC. [US/US]; Suite 1269, 300 Delaware Avenue, Wilmington, DE 19801 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ROBIN, Mark, L. [US/US]; 5415 Hillside Lane, West Lafayette, IN 47906 (US). ROWLAND, Thomas, F. [US/US]; 319 Pleasant Grove Road, El Dorado, AR 71730 (US).
- (74) Agent: HYTA, Robert, C.; Wells St. John, P.S., 601 W. 1st Avenue, Suite 1300, Spokane, WA 99201-3828 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

- with international search report
- (88) Date of publication of the international search report: 30 May 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

02/040102 A3

(54) Title: FIRE EXTINGUISHING METHODS UTILIZING HYDROFLUOROETHERS

(57) Abstract: Highly fluorinated, saturated and unsaturated hydrofluoroethers are efficient, economical, non-ozone-depleting fire extinguishing agents used alone or in blends with other fire extinguishing agents in total flooding and portable systems.

formation on patent family members


Inter Inal Application No
PCT7US 01/44256

						PC1/U3	01/44256
	atent document d in search report		Publication date		Patent family member(s)		Publication date
US	5730894	Α	24-03-1998	WO	9739081	A1	23-10-1997
WO	9640834	A	19-12-1996	EP JP WO	0830436 10506926 9640834	T	25-03-1998 07-07-1998 19-12-1996
WO	9324586	А	09-12-1993	US AT AU BR CN DE EP ES JP MX WO US US	5605882 177137 4250093 9306614 1082088 69323743 69323743 0642560 2130267 7507342 9303120 9324586 5648016 6416683 5779931	T A A A D 1 T 2 A 1 T 3 T A 1 A 1 A B 1	25-02-1997 15-03-1999 30-12-1993 08-12-1998 16-02-1994 08-04-1999 09-09-1999 15-03-1995 01-07-1999 10-08-1995 30-06-1994 09-12-1993 15-07-1997 09-07-2002 14-07-1998
US	6023002	A	08-02-2000	AU EP JP WO	7691198 1051381 2002501035 9937598	Al T	09-08-1999 15-11-2000 15-01-2002 29-07-1999
WO	0105468	Α	25-01-2001	AU EP WO US	6223600 1261398 0105468 6478979	A2 A2	05-02-2001 04-12-2002 25-01-2001 12-11-2002
	5562861	A	08-10-1996	US US AT AU BR CA CN DE EP JP RU US US US	5611210 5695688 193903 681640 6358794 9405991 2157567 1122606 69424935 0687287 8507524 2140955 9420588 5605647 5685915 5444102 5674451 5716549	A T B2 A A1 A1 A1 T C1 A1 A A	18-03-1997 09-12-1997 15-06-2000 04-09-1997 26-09-1994 26-12-1995 15-09-1994 15-05-1996 20-07-2000 20-12-1995 13-08-1996 10-11-1999 15-09-1994 25-02-1997 11-11-1997 22-08-1995 07-10-1997 10-02-1998
	2730543	A 	10-01-1956	NONE			
EP	0562858	A	29-09-1993	US US AT AU AU	5278342 5196600 186527 669604 5777894	A 7 T 8 B2	11-01-1994 23-03-1993 15-11-1999 13-06-1996 22-09-1994

Form PCT/ISA/210 (patent family annex) (July 1992)

Inte phal Application No PCT/US 01/44256

C.(Continua	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category *	Citation of document, with Indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 023 002 A (CHEBURKOV YURI ET AL) 8 February 2000 (2000-02-08) column 1, line 21 - line 30 column 3, line 20 - line 32 column 7, line 63 -column 8, line 5 column 11, line 8 - line 11	1,2,7,9
P,X	WO 01 05468 A (3M INNOVATIVE PROPERTIES CO) 25 January 2001 (2001-01-25) page 9, line 12 - line 25; table 1	1,4,7
P,A	FUKAYA H ET AL: "Fire extinguishing ability of perfluoroalkylamines and perfluoroethers evaluated by a small cup burner method" JOURNAL OF FLUORINE CHEMISTRY, ELSEVIER SEQUOIA, LAUSANNE, CH, vol. 106, no. 2, December 2000 (2000-12), pages 143-146, XP004219156 ISSN: 0022-1139 the whole document	1-9
A	US 5 562 861 A (NIMITZ JONATHAN S ET AL) 8 October 1996 (1996-10-08) column 14, line 25 - line 50; claims 1,11,13,14; table 4	1-9
Y	US 2 730 543 A (RENDALL JOHN L ET AL) 10 January 1956 (1956-01-10) column 1, line 44 - line 52 column 4, line 39 - line 45	11,12
Y	EP 0 562 858 A (HAMPSHIRE CHEMICAL CORP) 29 September 1993 (1993-09-29) claims 1-18; example 1	11,12
A	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 04, 31 May 1995 (1995-05-31) & JP 07 025803 A (AGENCY OF IND SCIENCE & TECHNOL; OTHERS: 04), 27 January 1995 (1995-01-27) abstract	10-12
A	US 3 557 294 A (GILBERT EVERETT E ET AL) 19 January 1971 (1971-01-19) column 2, line 57 - line 61	10-12
A	US 3 943 256 A (REGAN BERNARD M) 9 March 1976 (1976-03-09) column 2, line 17 - line 23	10-12
,		



Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)
This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
Claims Nos.:     because they relate to subject matter not required to be searched by this Authority, namely:
2. Claims Nos.: because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).
Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)
This International Searching Authority found multiple inventions in this international application, as follows:
see additional sheet
1. X As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
The additional search fees were accompanied by the applicant's protest.     X   No protest accompanied the payment of additional search fees.

Form PCT/ISA/210 (continuation of first sheet (1)) (July 1998)

formation on patent family members

Inter, mal Application No
PCT/US 01/44256

	Patent document ed in search report		Publication date		Patent family member(s)	Publication date
E	0562858	A		BR CA CN DE DE EP ES JP	9401152 A 2118828 AI 1100711 A 69326970 DI 69326970 T2 0562858 AI 2139626 T3 6298693 A	,B 29-03-1995 16-12-1999 2 29-06-2000 29-09-1993
JI	07025803	Α	27-01-1995	JP	2589917 B2	2 12-03-1997
Ü	3557294	Α	19-01-1971	NONE		
U	3943256	A	09-03-1976	BE FR GB US ZA	813867 A1 2233986 A1 1469423 A 3976788 A 7403055 A	

## FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-9

A method for extinguishing a fire and a fire extinguishing agent comprising a saturated, fluorinated C4 or C5 hydrofluoroether, or an unsaturated, fluorinated C4 or C5 hydrofluoroether

2. Claims: 10-12

A method of making saturated, fluorinated C4 or C5 hydrofluoroether

BNSDOCID: <WO\_\_\_\_\_0240102A3\_I\_>